

SAFETY DATA SHEET

1. Identification

Product identifier V1R11Series

Other means of identification

Synonyms HR PA-12 GB Powder

Recommended use Materials to be processed in HP 3D MJF equipment only.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

HP Inc.

1501 Page Mill Road Palo Alto, CA 94304-1112

United States

Telephone 650-857-5020

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048

HP Inc. Customer Care

_ine

(Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word Warning

Hazard statement May form combustible dust concentrations in air.

Precautionary statement

Prevention Take precautionary measures against static discharge. Use with adequate ventilation. Avoid

generation or accumulation of dust.

Response If inhaled, remove to fresh air. Get medical attention if symptoms persist. IN CASE OF FIRE, use

water spray or fog, foam, dry chemical or CO2. Collect in a chemical waste container. Use only

vacuum cleaners approved for combustible dust collection.

Storage Not available.

Disposal Not available.

Hazard(s) not otherwise

May form combustible dust concentrations in air.

classified (HNOC) Risk of skin burns caused by hot melt.

Supplemental informationThis material is considered hazardous under the OSHA Hazard Communication Standard criteria,

based on hazard(s) not otherwise classified.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Polyamide, Modified Polymer*		Proprietary*	100

Material name: V1R11Series sps us

14388 Version #: 04 Revision date: 06-Jun-2018 Issue date: 27-Nov-2017

This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard Communication Standard).

4. First-aid measures

Inhalation

If dust from the material is inhaled, remove the affected person immediately to fresh air.

Move to fresh air in case of accidental inhalation of vapors or decomposition products. If breathing is difficult, give oxygen. Oxygen or artificial respiration if needed. Consult a physician for specific

advice.

Skin contact Wash the skin immediately with soap and water. In case of contact with molten product, cool

rapidly with water and seek immediate medical attention. Do not attempt to remove molten product

from skin because skin will tear easily.

Eye contact Dust: Wash well-open eyes immediately, abundantly and thoroughly with water. Remove particle

remaining under the eyelids. If irritation persists, consult a doctor.

On contact with hot product: Cool eyes rapidly with cold water after contact with molten polymer.

Continue to rinse for at least 15 minutes. Get medical attention immediately.

No experiences of acute or chronic damages in humans have been made yet.

Ingestion If swallowed, do NOT induce vomiting. Get medical attention. Never give anything by mouth to an

unconscious person.

Most important

General information

symptoms/effects, acute and

delayed

d

Risk of skin burn caused by hot melt. Do not leave the victim unattended.

Remove victim immediately from source of exposure.

Water spray, foam, dry powder or carbon dioxide.

Victim to lie down in the recovery position, cover and keep him warm.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Do not use water jet as an extinguisher, as this will spread the line.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

General fire hazards

May be released in case of fire: carbon monoxide, carbon dioxide, nitric oxides, organic products of decomposition. Under certain fire conditions, traces of other toxic products may occur.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Do not use a solid stream of water. A solid stream of water can cause a dust explosion. Fire fighting equipment should be thoroughly decontaminated after use.

Dust clouds generated during handling and/or storage can form explosive mixtures with air. Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact

with the material or its container.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures In case product dust is released: Dust mask

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable container for disposal. If a vacuum is used, the motor must be rated as dust explosion-proof. Dispose of in compliance with federal, state, and local regulations.

Environmental precautions

Prevent further leakage or spillage. Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes Avoid breathing dust. Prevent dust accumulation to minimize explosion hazard. Inside and outside the equipment should be cleaned regularly with an explosion-protected vacuum cleaner to avoid dust accumulation. Do not sweep the dust or or try to remove it with a compressed-air gun. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Conditions for safe storage, including any incompatibilities

Store away from moisture and heat to maintain the technical properties of the product. Eliminate sources of ignition. Do not expose to heat or store above 60 C.

Material name: V1R11Series sps us

8. Exposure controls/personal protection

Occupational exposure limits

Also see Exposure guidelines.

ACGIH

 Material
 Type
 Value

 V1R11Series
 TWA
 10 mg/m3

Comments:

Inhalable particles

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Exposure Limit For Dust

ACGIH (TWA/TLV): 3 mg/m3 (Respirable Particulate) US CA OEL (TWA/PEL): 10 mg/m3 (Total dust) US CA OEL (TWA/PEL): 5 mg/m3 (Respirable fraction)

US OSHA (TWA:Z-3): 50millions of particles per cubic foot of air (Total dust)

US OSHA (TWA:Z-3): 15millions of particles per cubic foot of air (Respirable fraction)

US OSHA (TWA:Z-3): 5 mg/m3 (Respirable fraction) US OSHA (TWA:Z-3): 15 mg/m3 (Total dust)

Glass, oxide, chemicals

ACGIH (TWA/TLV): 1 fibers/cm3 (Fiber) F: Respirable fibers: length > 5 micrometers; aspect ration >= 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm

objective), using phase-contrast illumination. US CA OEL (TWA/PEL): .2 fibers/cm3 (Fiber)

Appropriate engineering controls

HP recommends the use of HP accessories for unpacking 3D parts and refilling the build chamber. If other methods are used, read the following: Dust clouds generated during handling and/or storage can form explosive mixtures with air. Dust explosion characteristics vary with the particle size, particle shape, moisture content, contaminants, and other variables. Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to fall freely or be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container.

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Consult ACGIH ventilation manual, NFPA Standard 91 and NFPA Standard 654 for design of exhaust system and safe handling.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields.

Skin protection

Other

Hand protection

Wear impermeable gloves. Protective heat-insulating gloves are to be used during thermal processing. Any areas of skin covered with dust must be washed immediately with soap and water

as the powder draws out natural moisture from the skin. Use barrier cream regularly.

as the powder draws out natural moisture from the skin. Ose barrier cream regularly.

Processing of this product releases vapors or fumes which may cause skin irritation. It is a good industrial hygiene practice to minimize skin contact. Wash thoroughly after handling.

Respiratory protection

Avoid breathing dust. Avoid breathing processing fumes or vapors. Where airborne exposure is likely or airborne exposure limits are exceeded, use NIOSH approved respiratory protection equipment appropriate to the material and/or its components and substances released during

processing.

Thermal hazards

In thermal processing: Risk of skin burns. Wear appropriate thermal protective clothing, when

necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Powder. Solid.

Material name: V1R11Series sps us

Physical stateNot available.FormPowder.ColorGrey to white.

Odor Not available.

Odor threshold Not available.

PH Not available.

Melting point/freezing point 363.2 - 368.6 °F (184 - 187 °C)

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature > 662 °F (> 350 °C)

Viscosity Not available.

Other information

Explosive properties Dusts might form explosive mixtures with air.

Powder explosivity data:

Minimum Ignition Energy (MIE) "dust cloud" w/ Inductance >30mJ. Layer Ignition Temperature (LIT) "dust layer" >400degC. Minimum Ignition Temperature (MIT) "dust cloud" >360degC.

Auto Ignition Temperature (AIT) >400degC.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity Under normal conditions: stable.

Chemical stabilityThe product is stable under normal handling and storage conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Take measures to mitigate material spillage and avoid potential ignition sources such as ESD

(ElectroStatic Discharges), flames, and sparks. Do not smoke nearby. Avoid wet/humid

environment. Recommended working humidity 50-70%. Avoid dust formation.

Incompatible materials Oxidizing materials, acids, strong bases, water and high humidity.

Hazardous decomposition

products

Decomposition products on thermal decomposition, carbon monoxide, carbon dioxide, Nitrogen

oxides (NOx), organic products of decomposition.

11. Toxicological information

Information on likely routes of exposure

Inhalation At high temperature, products of thermal decomposition can be irritating to respiratory system.

Skin contact May be considered as comparable to a similar product for which experimental results are: Non

irritating to skin.

May be considered as comparable to a similar product for which experimental results are: Not Eye contact

irritating to the eyes.

Ingestion May be considered as comparable to a similar product for which experimental results are: Slightly

harmful by ingestion.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Based on available data, the classification criteria are not met. Acute toxicity Based on available data, the classification criteria are not met. Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Based on available data, the classification criteria are not met. Respiratory sensitization Based on available data, the classification criteria are not met. Skin sensitization Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. **Aspiration hazard Further information** Complete toxicity data are not available for this specific formulation

12. Ecological information

Ecotoxicity No ecotoxicity data noted for the ingredient(s).

Persistence and degradability Not available. Bioaccumulative potential Not available. Not available. Mobility in soil Not available. Other adverse effects

13. Disposal considerations

Disposal instructions Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

Further information Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

Material name: V1R11Series SDS US

15. Regulatory information

US federal regulations US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA

All ingredients are listed or exempt.

US TSCA 12(b): Does not contain listed chemicals.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations Not Listed

under chemical substances notification laws in the following countries: US (TSCA), EU

(EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

16. Other information, including date of preparation or last revision

Issue date27-Nov-2017Revision date06-Jun-2018

Version # 04

Other information This SDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

Disclaimer This Safety Data Sheet document is provided without charge to customers of HP. Data is the most

current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other

countries.

Revision information 1. Product and Company Identification: Alternate Trade Names

Material name: V1R11Series SDS US

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: V1R11Series sps us